



N
HY-NT10/72GDF

590~610W

--	--	--	--	--	--	--

STC :	1000W/m ²	25	=1.5			
	(Pmpp/Wp)	590	595	600	605	610
	(Vmpp/V)	44.15	44.34	44.54	44.74	44.94
	(mpp/A)	13.37	13.42	13.48	13.53	13.58
	(Voc/V)	52.20	52.35	52.55	52.75	52.95
	(Isc/A)	14.13	14.19	14.25	14.31	14.37
		22.8%	23.0%	23.2%	23.4%	23.6%

NMOT :	800W/m²	20		=1.5		1m/s
	(Pmpp/Wp)	444.9	449.5	453.4	457.6	461.9
	(Vmpp/V)	41.50	41.70	41.90	42.10	42.30
	(mpp/A)	10.72	10.78	10.82	10.87	10.92
	(Voc/V)	49.64	49.84	50.04	50.24	50.44
	(Isc/A)	11.41	11.46	11.51	11.56	11.61

(600W)

Pmpp/Wp	Vmpp/V	Impp/A	Voc/V	Isc/A
5%				
15%				
25%				
	(Pmpp)		-0.29%/	
	(Isc)		+0.043%/	
	(Voc)		-0.24%/	
	(NMOT)		42	2°C

--

--

--

--

--

--

--

--

--